

=> file reg

FILE 'REGISTRY' ENTERED AT 13:52:02 ON 16 AUG 2005
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.
COPYRIGHT (C) 2005 American Chemical Society (ACS)

=> d his

FILE 'HCAPLUS' ENTERED AT 12:15:13 ON 16 AUG 2005

L1 20840 S MIYAMOTO ?/AU
L2 745 S TAYAMA ?/AU
L3 34 S L1 AND L2
L4 3101 S MIYAMOTO K?/AU
L5 200 S TAYAMA T?/AU
L6 0 S L4 AND L5
L7 2528 S MIYAMOTO M?/AU
L8 34 S L5 AND L7
L9 173643 S BRANCH? OR BRANCH?/TI
L10 11 S L8 AND L9
L11 62672 S POLYCARBONATE# OR POLY(A) CARBONATE#
L12 11 S L10 AND L11
SEL L12 9 RN

FILE 'REGISTRY' ENTERED AT 12:23:35 ON 16 AUG 2005

L13 7 S E1-E7
SEL L13 1,2,3,4,5 RN
L14 5 S E8-E12

FILE 'HCA' ENTERED AT 12:27:48 ON 16 AUG 2005

L15 12 S L14
L16 68476 S POLYCARBONATE# OR CARBONATE#(2A) (POLY OR POLYM? OR COPO
L17 8 S L15 AND L16

FILE 'LREGISTRY' ENTERED AT 12:35:17 ON 16 AUG 2005

L18 STR
L19 STR L18

FILE 'REGISTRY' ENTERED AT 13:32:05 ON 16 AUG 2005

E POLYCARBONATE/PCT
L20 17966 S E3
L21 STR L18
L22 STR L19
L23 1 S (L21 OR L22) SSS SAM SUB=L20
L24 9 S (L21 OR L22) SSS FUL SUB=L20
SAV L24 BOY672/A


FILE 'HCA' ENTERED AT 13:49:23 ON 16 AUG 2005

L25 11 S L24
L26 15 S L17 OR L25

FILE 'REGISTRY' ENTERED AT 13:52:02 ON 16 AUG 2005

=> d l24 que stat

L20 17966 SEA FILE=REGISTRY POLYCARBONATE/PCT
L21 STR



VAR G1=25/28/O/S/42

VAR G2=12/11/13

NODE ATTRIBUTES:

CONNECT IS E2 RC AT 25

CONNECT IS E2 RC AT 28

DEFAULT MLEVEL IS ATOM

DEFAULT ECLEVEL IS LIMITED

ECOUNT IS M1-X8 C AT 25

ECOUNT IS M5-X15 C AT 28


GRAPH ATTRIBUTES:

RING(S) ARE ISOLATED OR EMBEDDED

NUMBER OF NODES IS 31

STEREO ATTRIBUTES: NONE

L22 STR



VAR G2=12/11/13

NODE ATTRIBUTES:

CONNECT IS E2 RC AT 25

CONNECT IS E2 RC AT 28

DEFAULT MLEVEL IS ATOM

DEFAULT ECLEVEL IS LIMITED

ECOUNT IS M1-X8 C AT 25

ECOUNT IS M5-X15 C AT 28

GRAPH ATTRIBUTES:

RING(S) ARE ISOLATED OR EMBEDDED

NUMBER OF NODES IS 30

STEREO ATTRIBUTES: NONE

L24 9 SEA FILE=REGISTRY SUB=L20 SSS FUL (L21 OR L22)

100.0% PROCESSED 1912 ITERATIONS

9 ANSWERS

SEARCH TIME: 00.00.01

=> file hca

FILE 'HCA' ENTERED AT 13:52:13 ON 16 AUG 2005

USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.

PLEASE SEE "HELP USAGETERMS" FOR DETAILS.

COPYRIGHT (C) 2005 AMERICAN CHEMICAL SOCIETY (ACS)

=> d 126 1-15 cbib abs hitstr hitind

L26 ANSWER 1 OF 15 HCA COPYRIGHT 2005 ACS on STN

138:402692 Aromatic **polycarbonate** compositions with good moldability and high mechanical strength. Yokota, Koshiro; Hachiya, Hiroshi (Asahi Kasei Corporation, Japan). Jpn. Kokai Tokkyo Koho JP 2003155408 A2 20030530, 16 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 2001-356485 20011121.


AB The compns. contain 100 parts arom. **polycarbonates** (Mw 10,000-30,000) having structural repeating units OArO₂C (Ar = bivalent C₅-200 arom. group) and 0.015-0.5% ester groups directly bonded to main chains, 5-200 parts copolymers manufd. by grafting arom. vinyl compds. and vinyl cyanides onto diene rubbers, and 5-200 parts glass fibers. Thus, pellets comprising bisphenol A-based **polycarbonate** (Mw 19,500; ester content 0.016%, phenolic OH end group content 0.076%) manufd. by transesterification 100, ABS Resin RC (ABS rubber) 50, and ER 740 (glass roving) 20 parts were injection-molded to give a test piece showing Izod impact strength .gtoreq.10 kg/cm and flexural modulus .gtoreq.60,000 kg/cm². No deposition was obsd. in an injection mold until molding 8500 times.

IT **101949-49-9D, polycarbonates** with bisphenol A and carbonic acid diesters

(ABS rubber and glass fiber blends, impact-resistant; arom. **polycarbonate** compns. with good moldability and high mech. strength)

RN 101949-49-9 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
(CA INDEX NAME)



IC ICM C08L069-00

ICS C08G064-06; C08K007-14; C08L051-04

CC 37-6 (Plastics Manufacture and Processing)

ST arom **polycarbonate** ABS rubber impact resistance; ester
arom **polycarbonate** glass fiber moldability; grafted rubber
polycarbonate glass fiber strength

IT Glass roving

(aminosilane-treated, **polycarbonate** and ABS rubber blends, impact-resistant; arom. **polycarbonate** compns. with good moldability and high mech. strength)

IT Impact-resistant materials

(arom. **polycarbonate** compns. with good moldability and

- high mech. strength)
- IT **Polycarbonates**, uses
(arom., ester group-contg., ABS rubber and glass fiber blends, impact-resistant; arom. **polycarbonate** compns. with good moldability and high mech. strength)
- IT Reinforced plastics
(glass fiber-reinforced; arom. **polycarbonate** compns. with good moldability and high mech. strength)
- IT ABS rubber
(graft, **polycarbonate** and glass fiber blends, impact-resistant; arom. **polycarbonate** compns. with good moldability and high mech. strength)
- IT 80-05-7D, Bisphenol A, **polycarbonates** with carbonic acid diesters, ester group-contg. **101949-49-9D**, **polycarbonates** with bisphenol A and carbonic acid diesters (ABS rubber and glass fiber blends, impact-resistant; arom. **polycarbonate** compns. with good moldability and high mech. strength)
- IT 106677-58-1
(abs rubber, graft, **polycarbonate** and glass fiber blends, impact-resistant; arom. **polycarbonate** compns. with good moldability and high mech. strength)
- IT 463-79-6D, Carbonic acid, diesters, **polycarbonates** with arom. dihydroxy compds.
(graft copolymer and glass fiber blends, impact-resistant; arom. **polycarbonate** compns. with good moldability and high mech. strength)
- IT 331424-20-5, ER 740
(**polycarbonate** and ABS rubber blends, impact-resistant; arom. **polycarbonate** compns. with good moldability and high mech. strength)
- L26 ANSWER 2 OF 15 HCA COPYRIGHT 2005 ACS on STN
138:402681 Aromatic **polycarbonate** compositions with improved impact resistance. Yokota, Koshiro; Hachiya, Hiroshi (Asahi Kasei Corporation, Japan). Jpn. Kokai Tokkyo Koho JP 2003155337 A2 20030527, 16 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 2001-356484 20011121.
- AB The compns. with high strength and flowability, scarcely staining molds in molding process, comprise (A) arom. **polycarbonates** having repeating units OArO₂C (Ar = divalent C₅-200 arom. residue), content of ester groups directly bonded to main chains 0.015-0.5%, and wt.-av. mol. wt. 10,000-30,000 100, (B) diene rubber-arom. vinyl compd.-vinyl cyanide graft copolymers 5-200, and (C) carbon fibers 5-200 parts. Thus, a compn. contg. bisphenol A-based **polycarbonate**, ABS Resin RC (acrylonitrile-butadiene-styrene graft copolymer), and Besfight HTA-C 6U (carbon fiber) was injection-molded to give a test piece showing notched Izod impact


strength .gtoreq.10 kg-cm/cm.

IT **101949-49-9D, polycarbonate**

(arom. **polycarbonate**-graft copolymer-carbon fiber blends with improved impact resistance)

RN 101949-49-9 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
(CA INDEX NAME)



IC ICM C08G064-04

ICS C08G064-42; C08K007-06; C08L055-02; C08L069-00

CC 37-6 (Plastics Manufacture and Processing)

ST arom **polycarbonate** graft copolymer carbon fiber blend;
impact resistance arom **polycarbonate** blend; bisphenol A
polycarbonate ABS resin carbon fiber blend; ABS graft
copolymer **polycarbonate** carbon fiber blend

IT Carbon fibers, uses

(Besfight HTA-C 6U; arom. **polycarbonate**-graft
copolymer-carbon fiber blends with improved impact resistance)

IT Impact-resistant materials

(arom. **polycarbonate**-graft copolymer-carbon fiber
blends with improved impact resistance)

IT Polymer blends

(arom. **polycarbonate**-graft copolymer-carbon fiber
blends with improved impact resistance)

IT **Polycarbonates**, uses

(arom.; arom. **polycarbonate**-graft copolymer-carbon
fiber blends with improved impact resistance)

IT 106677-58-1, ABS graft copolymer

(ABS Resin RC; arom. **polycarbonate**-graft
copolymer-carbon fiber blends with improved impact resistance)

IT 80-05-7D, Bisphenol A, **polycarbonate 101949-49-9D**

, **polycarbonate**

(arom. **polycarbonate**-graft copolymer-carbon fiber
blends with improved impact resistance)


L26 ANSWER 3 OF 15 HCA COPYRIGHT 2005 ACS on STN

138:123601 Aromatic polycarbonate composition and recording disk


substrate prepared therefrom. Funakoshi, Wataru; Miyoshi, Takanori;
Kageyama, Yuichi; Sasaki, Katsushi (Teijin Ltd., Japan). Jpn. Kokai

Tokkyo Koho JP 2003026913 A2 20030129, 19 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 2002-108894 20020411. PRIORITY: JP 2001-120029 20010418.


GI



I



II



III

AB Optical recording media substrate, which is accurate and recyclable, is prepd. from arom. polycarbonate compn. contg. 100 parts of polycarbonate consisting at least one repeating unit selected from I, II, and III, in which R1-13 = H, C1-10 alkyl, C7-10 aralkyl, and C1-6 aryl, W = C2-10 alkylidene, C1-10 alkylene, C5-10 cycloalkylidene, C5-10 cycloalkylene, O, S, sulfoxide, and sulfone, n = 0-2, X1-3, Y1-2,4 = C1-5 alkylene, Z = C1-6 hydrocarbonyl with a carbon atom having three linkage points, 0.005-0.2 parts of ester formed by C10-25 aliph. monocarboxylic acid and C2-10 aliph. multivalent alc., and, optionally, 0.000001-0.01 parts of phosphorous oxyacid. The arom. polycarbonate is obtained by transesterification of arom. dihydroxy compd and diester carbonate in the presence of alkali metal catalysts selected from Li, K, Ru compds. Thus, phenyl-terminated polycarbonate prepd. from bisphenol A, diphenylcarbonate, and 2-methoxycarbonylphenylphenyl carbonate, glycerol monostearate 350 ppm, and tris(2,4-di-t-butylphenyl)phosphate 50 ppm were coextruded at 290.degree. to obtain a polycarbonate compn.

IT **443302-41-8P**

(arom. polycarbonate compn. for recording disk substrate)


RN 443302-41-8 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]-,
polymer with diphenyl carbonate and 4,4'-(1-
methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 101949-49-9


CMF C16 H16 O4



CM 2

CRN 102-09-0


CMF C13 H10 O3



CM 3

CRN 80-05-7


CMF C15 H16 O2




IC ICM C08L069-00

ICS C08G064-04; C08G064-30; C08J005-18; C08K003-32; C08K005-103;
G11B007-24; G11B011-105


- CC 38-3 (Plastics Fabrication and Uses)
Section cross-reference(s): 37, 74
- IT 24936-68-3P, Bisphenol A-diphenylcarbonate copolymer, sru, uses
25929-04-8P, Bisphenol A-diphenylcarbonate copolymer
189010-65-9DP, 2-Methoxycarbonylphenylphenyl carbonate, reaction
products with polycarbonate **443302-41-8P**
(arom. polycarbonate compn. for recording disk substrate)
- L26 ANSWER 4 OF 15 HCA COPYRIGHT 2005 ACS on STN
137:170327 Branched aromatic **polycarbonate** and process for
producing the same. Miyamoto, Masaaki; Tayama, Takao (Mitsubishi
Chemical Corporation, Japan). PCT Int. Appl. WO 2002062870 A1
20020815, 26 pp. DESIGNATED STATES: W: AE, AG, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ,
EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW, AM, AZ, BY, KG, KZ,
MD, RU, TJ, TM; RW: AT, BE, BF, BJ, CF, CG, CH, CI, CM, CY, DE, DK,
ES, FI, FR, GA, GB, GR, IE, IT, LU, MC, ML, MR, NE, NL, PT, SE, SN,
TD, TG, TR. (Japanese). CODEN: PIXXD2. APPLICATION: WO 2002-JP793
20020131. PRIORITY: JP 2001-29951 20010206.
- AB A branched arom. **polycarbonate** excellent in hue and melt
properties such as melt strength is obtained through
transesterification and has a viscosity-av. mol. wt. of 16,000 or
higher, where the amt. of structural units O-p-C6H4XA1CO,
O-p-C6H4XA2CO and O-p-C6H4XA3CO (A1 = 4-hydroxy-1,3-phenylene
provided that the position connecting to CO is 3; A2 =
2-hydroxy-1,3-phenylene provided that the position connecting to CO
is 3; A3 = 2-hydroxy-1,5-phenylene provided that the position
connecting to CO is 5; X = direct bond or linking groups) in main
chain derived from the site transfer reaction during
transesterification reaction are at 2,000-50,000, 30-10,000 and
30-10,000 wt. ppm, resp.
- IT **101949-49-9P 446246-17-9P 446246-18-0P**
446246-19-1P 446246-20-4P
(branched arom. **polycarbonates** contg. sub-structures
derived from carboxybisphenols produced by transfer reaction of
carbonate groups)
- RN 101949-49-9 HCA
- CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
(CA INDEX NAME)




RN 446246-17-9 HCA
 CN Benzoic acid, 2-hydroxy-3-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
 (CA INDEX NAME)




RN 446246-18-0 HCA
 CN Benzoic acid, 4-hydroxy-3-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
 (CA INDEX NAME)



RN 446246-19-1 HCA
 CN Benzoic acid, 3,3'-[oxybis[4,1-phenylene(1-methylethylidene)]]bis[6-hydroxy- (9CI) (CA INDEX NAME)



RN 446246-20-4 HCA
 CN Benzoic acid, 2,2'-oxybis[5-[1-(4-hydroxyphenyl)-1-methylethyl]-
 (9CI) (CA INDEX NAME)



IC ICM C08G064-14
 CC 37-3 (Plastics Manufacture and Processing)
 Section cross-reference(s): 35
 ST bisphenol **polycarbonate** branching structure hue melt
 strength relation
 IT **Polycarbonates**, preparation
 (bisphenol-based; branched arom. **polycarbonate** and
 process for producing same)
 IT Polymer chains
 (branched arom. **polycarbonate** and process for producing
 same)
 IT 24936-68-3P, Bisphenol A-diphenyl **carbonate**
copolymer sru, preparation 25929-04-8P, Bisphenol
 A-diphenyl **carbonate copolymer**
 (branched arom. **polycarbonate** and process for producing
 same)
 IT **101949-49-9P 446246-17-9P 446246-18-0P**
446246-19-1P 446246-20-4P
 (branched arom. **polycarbonates** contg. sub-structures
 derived from carboxybisphenols produced by transfer reaction of
 carbonate groups)

L26 ANSWER 5 OF 15 HCA COPYRIGHT 2005 ACS on STN
 137:110005 Polycarbonate compositions with good transcript precision and
 laser disk substrates using them. Funakoshi, Wataru; Miyoshi,
 Takanori; Kageyama, Yuichi; Sasaki, Katsushi (Teijin Ltd., Japan).
 Jpn. Kokai Tokkyo Koho JP 2002212411 A2 20020731, 13 pp.
 (Japanese). CODEN: JKXXAF. APPLICATION: JP 2001-10001 20010118.
 AB The compns. contain 100 parts arom. polycarbonates having repeating
 units of OXWZOCO (X, Z = p-phenylene group optionally bearing C1-10
 alkyl, aralkyl or aryl groups; W = direct bond, alkylidene,
 alkylene, cycloalkylidene, cycloalkylene, phenyl-substituted
 alkylene, O, S, SO₂) and viscosity-av. mol. wt. of 12,000-17,000,
 and 0.005-0.2 parts C10-25 aliph. monocarboxylic acids and C2-10

aliph. polyalc. fatty acid esters, and have the enthalpy relaxation of 2.2-3.8 J/g, where the polycarbonates are prepd. by the melt polymn. of a bisphenol compd. with a carbonate group former in the presence of a transesterification catalyst. Thus, heating 137 parts a purified bisphenol A with 133 parts di-Ph carbonate in the presence of 7.1×10^{-5} parts bisphenol A di-Li salt and 5×10^{-3} parts tetramethylammonium hydroxide under N to 180.degree. until melting, stirring the resulting melt while pulling the pressure to 100 mm-Hg, reacting for 20 min while distg. off phenol, heating up to 200.degree. while distg. off phenol at 30 mm-Hg, slowly heating up and maintaining for 20 min each at 220.degree., 240.degree. and 260.degree., resp., pulling the pressure to 20 mm-Hg over 10 min then to 10 mm-Hg, after reacting for min, pulling the pressure to 0.5 mm-Hg and reacting at 260.degree. until a viscosity-av. mol. wt. of 15,3000 was reached, adding 7.2×10^{-4} parts dodecylbenzenesulfonic acid tetra-Bu phosphonium salt and mixing at 260.degree./0.5 mm-Hg for 10 min gave a polycarbonate with phenolic OH group content 130 equiv/ton-polycarbonate, phenoxy group content 191 equiv/ton-polycarbonate and branching rate 0.03 mol%. Molding a compn. of the polycarbonate contg. 300 ppm glycerol monostearate, 50 ppm tris(2,4-di-tert-butylphenyl) phosphite, 10% H₃PO₄ and 50% tri-Me phosphate gave test pieces with good detail transfer precision, enthalpy relaxation 2.4 J/g and Tg 145.degree..

IT **443302-41-8P**, Bisphenol A;2-(3-carboxy-4-hydroxyphenyl)-2-(4-hydroxyphenyl)propane;diphenyl carbonate copolymer
(polycarbonate compns. with good transcript precision and laser disk substrates using them)


RN 443302-41-8 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]-, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1


CRN 101949-49-9

CMF C16 H16 O4




CM 2

CRN 102-09-0
CMF C13 H10 O3



CM 3


CRN 80-05-7
CMF C15 H16 O2



IC ICM C08L069-00
ICS C08G064-30; C08K005-103; G11B007-24
CC 37-3 (Plastics Manufacture and Processing)
Section cross-reference(s): 76
IT 25037-45-0P, Bisphenol A polycarbonate 25929-04-8P, Bisphenol A-diphenyl carbonate copolymer 25971-63-5P, Bisphenol A-phosgene copolymer **443302-41-8P**, Bisphenol A;2-(3-carboxy-4-hydroxyphenyl)-2-(4-hydroxyphenyl)propane;diphenyl carbonate copolymer
(polycarbonate compns. with good transcript precision and laser disk substrates using them)

L26 ANSWER 6 OF 15 HCA COPYRIGHT 2005 ACS on STN
135:319061 Branched aromatic polycarbonates with improved fluidity under high load and their preparation. Miyamoto, Masaaki; Tayama, Takao (Mitsubishi Chemical Corp., Japan). Jpn. Kokai Tokkyo Koho JP 2001302780 A2 20011031, 13 pp. (Japanese). CODEN: JKXXAF.
APPLICATION: JP 2000-119494 20000420.

GI



AB The process is characterized by transesterification of carbonic diesters and arom. hydroxy compds. in the presence of .gtoreq.0.01 mol% (based on the arom. hydroxy compds.) branching agents bearing (esterified) carboxyl or halocarbonyl and .gtoreq.2 (/mol.) OH groups. The branching agents may be HOQ1XQ2OH or OHQ3XQ4OQ5XQ6OH [Q1-6 = p-C6H4 where Q1 and/or Q2 and .gtoreq.1 of Q3-6 bear (esterified) carboxyl or halocarbonyl; X = single bond, C1-8 alkylene, C2-8 alkylidene, C5-15 cycloalkyl(id)ene, O, S, CO, SO, SO2]. Thus, di-Ph carbonate 205.0, bisphenol A 197.1, and I 0.59 mol/h were transesterified in the presence of Cs carbonate and polycondensed to give an arom. polycarbonate showing yellowness index 2.5, melt index (21.6-kg load) 18.41, and author's defined branching coeff. (ratio of sample wt. extruded under 21.6-kg load and that under 2.16-kg load at 260.degree.) 20.5.

IT **368872-96-2P 368872-98-4P 368873-00-1P**

(prepn. of branched arom. polycarbonates with good yellowing resistance, heat stability, and improved fluidity under high load)


RN 368872-96-2 HCA

CN Benzoic acid, 3,3'-(1-methylethylidene)bis[6-hydroxy-, diphenyl ester, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 368872-95-1


CMF C29 H24 O6



CM 2

CRN 102-09-0


CMF C13 H10 O3



CM 3

CRN 80-05-7

CMF C15 H16 O2




RN 368872-98-4 HCA

CN Benzoic acid, 5-[1-(4-hydroxyphenyl)-1-methylethyl]-2-[4-[1-(4-hydroxyphenyl)-1-methylethyl]phenoxy]-, phenyl ester, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI)
(CA INDEX NAME)

CM 1

CRN 368872-97-3


CMF C37 H34 O5



CM 2

CRN 102-09-0


CMF C13 H10 O3



CM 3

CRN 80-05-7

CMF C15 H16 O2




RN 368873-00-1 HCA

CN Benzoic acid, 2,2'-oxybis[5-[1-(4-hydroxyphenyl)-1-methylethyl]-, diphenyl ester, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 368872-99-5


CMF C44 H38 O7



CM 2

CRN 102-09-0


CMF C13 H10 O3



CM 3

CRN 80-05-7

CMF C15 H16 O2



IC ICM C08G064-30

CC 37-3 (Plastics Manufacture and Processing)

Section cross-reference(s): 35, 38



IT **368872-96-2P 368872-98-4P 368873-00-1P**

(prepn. of branched arom. polycarbonates with good yellowing resistance, heat stability, and improved fluidity under high load)

L26 ANSWER 7 OF 15 HCA COPYRIGHT 2005 ACS on STN

126:226011 Copolycarbonate compositions with excellent moldability and molding color stability and surface appearances. Shimoda, Tomoaki; Sakashita, Takeshi (GE Plastics Japan Ltd, Japan). Jpn. Kokai Tokkyo Koho JP 09031316 A2 19970204 Heisei, 19 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 1995-205075 19950720.

GI



AB The title compns. comprise (A) copolycarbonates contg. arom. dihydroxy compd.-derived units I and II [X, Y = CR₃R₄, C(:R₅), O, S, SO, SO₂; R₁, R₂, R₇, R₈ = (halo) C₁-10 hydrocarbyl, halogen; R₃, R₄ = H, (halo)hydrocarbyl; R₅ = (halo)hydrocarbylene; m, n, p = 0-4; q = 0-3] and (B) fillers. Bisphenol A-2-(4-hydroxyphenyl)-2-(3-phenoxy-carbonyl-4-hydroxyphenyl)propane-diphenyl carbonate copolymer contg. 70 phr glass fiber and other usual additives showed good injection and blow moldability.

IT **167163-45-3P**

(copolycarbonate compns. with excellent moldability)


RN 167163-45-3 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]-, phenyl ester, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 167163-44-2


CMF C22 H20 O4



CM 2

CRN 102-09-0


CMF C13 H10 O3



CM 3

CRN 80-05-7

CMF C15 H16 O2



IC ICM C08L069-00

ICS C08K003-40; C08K005-04; C08K005-41; C08K005-52; C08K007-06;
C08K007-14

CC 37-6 (Plastics Manufacture and Processing)

IT **167163-45-3P**

(copolycarbonate compns. with excellent moldability)

L26 ANSWER 8 OF 15 HCA COPYRIGHT 2005 ACS on STN



126:226010 Copolycarbonate compositions with excellent moldability.

Shimoda, Tomoaki; Sakashita, Takeshi (GE Plastics Japan Ltd, Japan).

Jpn. Kokai Tokkyo Koho JP 09031317 A2 19970204 Heisei, 20 pp.

(Japanese). CODEN: JKXXAF. APPLICATION: JP 1995-205076 19950720.

GI



AB The title compns. comprise (A) copolycarbonates contg. arom. dihydroxy compd.-derived units I and II [X, Y = CR₃R₄, C(:R₅), O, S, SO, SO₂; R₁, R₂, R₇, R₈ = (halo) C₁₋₁₀ hydrocarbyl, halogen; R₃, R₄ = H, (halo)hydrocarbyl; R₅ = (halo)hydrocarbylene; m, n, p = 0-4; q = 0-3] and (B) other thermoplastic resins. A 60:40 blend of bisphenol A-2-(4-hydroxyphenyl)-2-(3-phenoxy-carbonyl-4-hydroxyphenyl)propane-diphenyl carbonate copolymer and PBT and other additives showed good injection and blow moldability.

IT **167163-45-3P**, Bisphenol A-diphenyl carbonate-2-(4-hydroxyphenyl)-2-(4-hydroxy-3-phenoxy-carbonylphenyl)propane copolymer

(copolycarbonate compns. with excellent moldability)


RN 167163-45-3 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]-, phenyl ester, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 167163-44-2


CMF C22 H20 O4



CM 2

CRN 102-09-0


CMF C13 H10 O3



CM 3

CRN 80-05-7

CMF C15 H16 O2





IC ICM C08L069-00
 ICS C07C065-105; C08K005-04; C08K005-41; C08K005-52; C08L033-12;
 C08L055-02; C08L067-02; C08L077-00; C08L079-08; C08L101-00
 CC 37-6 (Plastics Manufacture and Processing)
 IT **167163-45-3P**, Bisphenol A-diphenyl carbonate-2-(4-hydroxyphenyl)-2-(4-hydroxy-3-phenoxycarbonylphenyl)propane copolymer
 (copolycarbonate compns. with excellent moldability)

L26 ANSWER 9 OF 15 HCA COPYRIGHT 2005 ACS on STN
 125:249967 **Polycarbonates** for optical materials. Isawa,
 Kenichi; Kodaira, Tetsuji (GE Plastics Japan Ltd, Japan). Jpn.

Kokai Tokkyo Koho JP 08183842 A2 19960716 Heisei, 15 pp.
(Japanese). CODEN: JKXXAF. APPLICATION: JP 1994-339661 19941228.

GI



AB Title polymers, having viscosity-av. mol. wt. (Mv) 12,000-18,000, and useful for optical disks, lenses, etc., contain the repeating units of 1 mol I and 8 .times. 10⁻⁵ - 1.5 .times. 10⁻³ mol II [R1, R2, R7, R8 = (halo-substituted) C1-10 linear or cyclic hydrocarbonyl, halo; X, Z = R3CR4, C:R5, O, S, SO, SO2; R3, R4 = H, (halo-substituted) C1-15 linear, branched, or cyclic monovalent hydrocarbonyl; R5 = (halo-substituted) C1-15 linear, branched, or cyclic hydrocarbonylene; m, n = 0-4; p = 0-4; q = 0-3]. Thus, 0.433 mol 2-(4-hydroxyphenyl)-2-(3-phenoxy-carbonyl-4-hydroxyphenyl)propane was polymd. with 0.44 kmol bisphenol A and 0.46 kmol di-Ph carbonate to give a polymer with Mv 15,500, which was made into a compact disk showing low birefringence.

IT **167163-45-3P**

(prepn. of **polycarbonates** for optical materials)


RN 167163-45-3 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]-, phenyl ester, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 167163-44-2


CMF C22 H20 O4



CM 2

CRN 102-09-0


CMF C13 H10 O3



CM 3


CRN 80-05-7

CMF C15 H16 O2

IT **101949-49-9P**(prepn. of **polycarbonates** for optical materials)

RN 101949-49-9 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
(CA INDEX NAME)



- IC ICM C08G064-04
ICS G02B001-04
- CC 38-3 (Plastics Fabrication and Uses)
Section cross-reference(s): 35, 73
- ST **polycarbonate** bisphenol compact disk birefringence; arom
polycarbonate optical material
- IT Optical materials
(prepn. of **polycarbonates** for optical materials)
- IT Memory devices
(optical disks, read-only, prepn. of **polycarbonates** for
optical materials)
- IT Polyesters, uses
(**polycarbonate-**, arom., prepn. of
polycarbonates for optical materials)
- IT **Polycarbonates**, uses
(polyester-, arom., prepn. of **polycarbonates** for
optical materials)
- IT **167163-45-3P**
(prepn. of **polycarbonates** for optical materials)
- IT **101949-49-9P** 167163-44-2P
(prepn. of **polycarbonates** for optical materials)
- IT 102-09-0, Diphenyl carbonate 25088-71-5, Bisphenol A potassium
salt
(prepn. of **polycarbonates** for optical materials)

L26 ANSWER 10 OF 15 HCA COPYRIGHT 2005 ACS on STN

125:223563 Aromatic copolycarbonate compositions for optical products.
Isawa, Kenichi; Mori, Kenichi; Kodaira, Tetsuji (GE Plastics Japan
Ltd, Japan). Jpn. Kokai Tokkyo Koho JP 08183843 A2 19960716 Heisei,
15 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 1994-339664
19941228.

AB The title compns. contain (A) 100 parts copolycarbonates having
viscosity-av. mol. wt. 12,000-18,000 and contg. 1:(8 .times.
10-5-1.5 .times. 10-3) OC6H4-m(R1)mXC6H4-n(R2)nO and
OC6H4-p(R7)pYC6H3-q(R8)q(CO2)O [R1, R2, R7, R8 = C1-10
(halo)hydrocarbyl, halo; X, Y = CR3R4, C:R5, O, S, SO, SO2; R3, R4 =
H, C1-15 (halo)hydrocarbyl; R5 = C1-15 (halo)hydrocarbylidene; m, n,
p = 0-4; q = 0-3] and (B) 0.01-0.1 part aliph. carboxylic acid


polyalc. esters. Thus, 0.44 kmol bisphenol A, 0.433 mol 2-(4-hydroxyphenyl)-2-(3-phenoxy-carbonyl-4-hydroxyphenyl)propane (prepd. from bisphenol A K salt and CO₂), and 0.46 kmol Ph₂CO₃ were polymd. at 180-240.degree. under normal pressure to 15 mmHg for 1 h to give copolycarbonate, which (100 parts) was mixed with 0.05 part stearic acid monoglyceride to prep. a compact disk without stringiness.

IT **101949-49-9DP, polymers with carbonates**
167163-45-3P

(arom. copolycarbonate compns. for optical products)

RN 101949-49-9 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
 (CA INDEX NAME)




RN 167163-45-3 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]-, phenyl ester, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 167163-44-2


CMF C22 H20 O4



CM 2

CRN 102-09-0


CMF C13 H10 O3



CM 3

CRN 80-05-7


CMF C15 H16 O2

IT **101949-49-9P**

(arom. copolycarbonate compns. for optical products)

RN 101949-49-9 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
(CA INDEX NAME)



IC ICM C08G064-04

ICS C08K005-109; C08L069-00; G02B001-04; G02B007-02

CC 37-6 (Plastics Manufacture and Processing)

Section cross-reference(s): 38, 74

ST **polycarbonate** polyalc carboxylate optical productIT **Polycarbonates**, preparation

(arom., arom. copolycarbonate compns. for optical products)

IT **101949-49-9DP, polymers with carbonates****167163-45-3P**

(arom. copolycarbonate compns. for optical products)

IT **101949-49-9P** 167163-44-2P

(arom. copolycarbonate compns. for optical products)

L26 ANSWER 11 OF 15 HCA COPYRIGHT 2005 ACS on STN

123:144999 **Polycarbonates** and their manufacture. Sakashita, Takeshi; Shimoda, Tomoaki; Nagai, Koji (GE Plastics Japan Ltd, Japan). Jpn. Kokai Tokkyo Koho JP 07149887 A2 19950613 Heisei, 17 pp. (Japanese). CODEN: JKXXAF. APPLICATION: JP 1993-319281 19931126.

AB **Polycarbonates** with good melt elasticity, color, heat resistance, water resistance, and transparency are branched copolymers of .gtoreq.2 arom. diols including diols with an ester functionality and diesters of carbonic acid. 2-(4-Hydroxyphenyl)-2-(3'-phenoxy-carbonyl-4'-hydroxyphenyl)propane was synthesized and polymd. with bisphenol A and di-Ph carbonate (1.3 mol:0.44 mol:0.46 mol) to provide a transparent polymer with limiting viscosity 0.49 dl/g, melt flow rate 3.5 g/10 min, and acidic substance content 1.8 ppm.

IT **167163-45-3P**
(**polycarbonates** and their manuf.)


RN 167163-45-3 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]-, phenyl ester, polymer with diphenyl carbonate and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 167163-44-2


CMF C22 H20 O4



CM 2

CRN 102-09-0


CMF C13 H10 O3




CM 3

CRN 80-05-7

CMF C15 H16 O2

IT **101949-49-9P**(prepn. of arom. diols for manuf. of **polycarbonates**)

RN 101949-49-9 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
(CA INDEX NAME)

IC ICM C08G064-06

ICS C08G064-10; C08G064-30

CC 35-5 (Chemistry of Synthetic High Polymers)

ST **polycarbonate** arom manufIT **Polycarbonates**, preparation(arom., **polycarbonates** and their manuf.)

IT Polyesters, preparation

(**polycarbonate**-, arom., **polycarbonates** and
their manuf.)IT **Polycarbonates**, preparation(polyester-, arom., **polycarbonates** and their manuf.)

IT 778-28-9, Butyl p-toluenesulfonate 2082-79-3 2386-87-0

31570-04-4, Tris(2,4-di-tert-butylphenyl)phosphite

(**polycarbonate** compns.)IT **167163-45-3P**(**polycarbonates** and their manuf.)IT **101949-49-9P** 167163-44-2P(prepn. of arom. diols for manuf. of **polycarbonates**)

IT 80-05-7, reactions 102-09-0, Diphenyl carbonate 124-38-9, Carbon

dioxide, reactions

(prepn. of arom. diols for manuf. of **polycarbonates**)

L26 ANSWER 12 OF 15 HCA COPYRIGHT 2005 ACS on STN

121:206649 The chemistry of .gamma.-irradiated bisphenol-A

polycarbonate. Factor, A.; Carnahan, J. C.; Dorn, S. B.;

Van Dort, P. C. (GE Res. Development, Schenectady, NY, 12301, USA).

Polymer Degradation and Stability, 45(1), 127-37 (English) 1994.

CODEN: PDSTDW. ISSN: 0141-3910.

AB On exposure to sterilizing doses of 60Co .gamma.-rays, bisphenol A

polycarbonate (I) turns a moderately intense yellow color.

Product studies of .gamma.-ray irradiated I and a model compd., I

cyclic tetramer, were undertaken to define the major degradative

process involved, and to try to identify the chem. species

responsible for the color. The major irradiation products were isolated

and identified using base hydrolysis followed by HPLC/MS anal.

These studies showed that the principal degradative process induced

by .gamma.-ray irradiation involved Fries type free radical reactions

leading to the destruction of the carbonate linkages and formation

of a no. of phenol coupling products and salicylate esters.

Chromatog./spectroscopic studies indicated that the yellow color was

mainly due to the formation of two labile products having a broad

.lambda.max at .apprx.360nm. However, numerous attempts to isolate

and identify these compds. using HPLC/MS and GC/MS were


unsuccessful.

IT **101949-49-9**

(hydrolyzed radiochem. degradation products of bisphenol A carbonate
cyclic tetramer)

RN 101949-49-9 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
(CA INDEX NAME)



CC 37-4 (Plastics Manufacture and Processing)

Section cross-reference(s): 35, 36, 63

ST **polycarbonate** radiochem degradation product; sterilization

radiochem **polycarbonate**; yellowing **polycarbonate**

radiochem sterilization

IT Gamma ray

(the chem. of .gamma.-irradiated bisphenol A

- polycarbonate)**
IT **Polycarbonates**, properties
(the chem. of .gamma.-irradiated bisphenol A
polycarbonate)
IT Polymer degradation
Sterilization and Disinfection
(radiochem., the chem. of .gamma.-irradiated bisphenol A
polycarbonate)
IT Discoloration
(yellowing, radiochem.; the chem. of .gamma.-irradiated bisphenol
A **polycarbonate)**
IT **101949-49-9** 134296-36-9 158178-42-8 158178-43-9
158178-44-0 158178-45-1 158178-46-2 158178-47-3 158178-48-4
158178-49-5
(hydrolyzed radiochem. degrdn. products of bisphenol A carbonate
cyclic tetramer)
IT 21194-07-0 21194-07-0D, hydrolyzed 24936-68-3, Lexan 140,
properties 25037-45-0, Bisphenol A-carbonic acid copolymer
(the chem. of .gamma.-irradiated bisphenol A
polycarbonate)

L26 ANSWER 13 OF 15 HCA COPYRIGHT 2005 ACS on STN

113:116501 Polycarbonate crosslinking agents for fire-resistant
compositions. Rosenquist, Niles R. (General Electric Co., USA).
U.S. US 4912194 A 19900327, 6 pp. (English). CODEN: USXXAM.
APPLICATION: US 1988-280845 19881207.

AB Polycarbonates contg. the units $[-OC_6H_3(CO_2H)ZnC_6H_4(CO_2R)OCO-]$ $[Z =$
C1-15 (halo)alkylene; $n = 0$ or 1 ; $R = H$, (halo)hydrocarbyl] can be
crosslinked by heat. Thus, polymn. of bisphenol A 0.495, COCl₂ 0.6,
and di-Et 5,5'-methylenebis(2-hydroxybenzoate) (I) 0.005 mol gave a
resin, heating of which at 300.degree. for 60 min gave a crosslinked
resin with intrinsic viscosity 0.852 and gel content 15%, vs. 0.540
and 0, resp., without I.

IT **128248-95-3P**
(thermosetting, manuf. of)


RN 128248-95-3 HCA

CN Benzoic acid, 3,3'-methylenebis[6-hydroxy-, diethyl ester, polymer
with carbonic dichloride and 4,4'-(1-methylethylidene)bis[phenol]
(9CI) (CA INDEX NAME)

CM 1

CRN 28269-32-1


CMF C19 H20 O6



CM 2

CRN 80-05-7


CMF C15 H16 O2



CM 3

CRN 75-44-5

CMF C C12 O



IC ICM C08G063-64

INCL 528196000

CC 37-6 (Plastics Manufacture and Processing)

IT **128248-95-3P**

(thermosetting, manuf. of)

L26 ANSWER 14 OF 15 HCA COPYRIGHT 2005 ACS on STN

107:154968 Cyclic oligocarbonates. Rosenquist, Niles Richard (General Electric Co., USA). Ger. Offen. DE 3638260 A1 19870514, 9 pp.

(German). CODEN: GWXXBX. APPLICATION: DE 1986-3638260 19861110.

PRIORITY: US 1985-796984 19851112.

AB Cyclic oligocarbonates (d.p. 2-16) which can be polymd. in situ to high-mol. wt. polycarbonates contain bisphenols and carboalkoxylated

(degree of substitution 1-4) bisphenols. Adding COCl_2 at 2.0 g/min to bisphenol A 44.7, di-Me 5,5'-methylenebis(2-hydroxybenzoate) 1.26, and H_2O 200 g and 200 mL CH_2Cl_2 with stirring for 21 min, with addn. of 25% NaOH to maintain a pH of 2-5 and adding the resulting CH_2Cl_2 soln. over 1 h to 6.4 mL Et_3N , 80 g 50% NaOH, 120 mL H_2O , and 300 mL CH_2Cl_2 with stirring gave 24 g acetone-sol. cyclic oligomers. Heating 6 g oligomers contg. 9 mg $\text{Me}_4\text{N}^+ \text{BPh}_4^-$ at 120.degree. for 4 h and pressing a film at 250.degree. for 20 min gave a product contg. 41% gel and 59% acetone-sol. polymer with intrinsic viscosity (CH_2Cl_2 , 25.degree.) 1.97 dL/g.

IT **110563-08-1P**

(cyclic, oligomeric, manuf. of)


RN 110563-08-1 HCA

CN Benzoic acid, 3,3'-methylenebis[6-hydroxy-, dimethyl ester, polymer with carbonic dichloride and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 28505-57-9


CMF C17 H16 O6



CM 2


CRN 80-05-7

CMF C15 H16 O2



CM 3


CRN 75-44-5
CMF C Cl2 O



IC ICM C07D323-00
ICS C07D327-00; C08G063-62; C08L069-00; C08J005-04; C08J005-24
ICA C08G075-00; C08G065-48; C08G067-00
CC 35-5 (Chemistry of Synthetic High Polymers)
IT **110563-08-1P**
(cyclic, oligomeric, manuf. of)

L26 ANSWER 15 OF 15 HCA COPYRIGHT 2005 ACS on STN
104:207918 Branched **polycarbonate** from carboxy-containing
diphenol. Mark, Victor; Hedges, Charles V. (General Electric Co.,
USA). U.S. US 4562242 A 19851231, 7 pp. (English). CODEN:
USXXAM. APPLICATION: US 1984-685907 19841224.

GI




AB High-mol.-wt. thermoplastic, randomly branched
polycarbonates (intrinsic viscosity 0.3-2 dL/g, CH₂Cl₂,
25.degree.) made from an arom. dihydric phenol, a carbonate
precursor, and a chain-branching agent comprises .gtoreq.1 I (z =
C4-6 cycloalkylidene; R, R1 = halogen, C1-4 hydrocarbon,
hydrocarbonoxy; n, p, p' = 0, 1). For example, 57.1 g
2,2-bis(4-hydroxyphenyl)propane, 0.75 g PhOH, 0.7 mL triethylamine,
400 mL Me₂Cl₂, 300 mL H₂O, 0.25 g 2,2'-dihydroxy-5,5'-
methylenebis(benzoic acid), and 36 g phosgene were reacted. The
branched **polycarbonate**, pptd. with MeOH, had intrinsic
viscosity 0.563 dL/g and modified melt flow value (ASTM D 1238,
300.degree.) 95, 10 s.

IT **101949-49-9**
(branching agents, for **polycarbonates**)

RN 101949-49-9 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]- (9CI)
(CA INDEX NAME)



IT **101949-50-2P 101964-29-8P**

(manuf. of branched)


RN 101949-50-2 HCA

CN Benzoic acid, 2-hydroxy-5-[1-(4-hydroxyphenyl)-1-methylethyl]-, polymer with carbonic dichloride and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 101949-49-9


CMF C16 H16 O4



CM 2

CRN 80-05-7


CMF C15 H16 O2



CM 3

CRN 75-44-5

CMF C C12 O




RN 101964-29-8 HCA

CN Benzoic acid, 3,3'-methylenebis[6-hydroxy-, polymer with carbonic dichloride and 4,4'-(1-methylethylidene)bis[phenol] (9CI) (CA INDEX NAME)

CM 1

CRN 122-25-8


CMF C15 H12 O6



CM 2

CRN 80-05-7


CMF C15 H16 O2



CM 3

CRN 75-44-5

CMF C C12 O



IC ICM C08G063-62
INCL 528193000
CC 35-5 (Chemistry of Synthetic High Polymers)
ST branched **polycarbonate** carboxybisphenol
IT **Polycarbonates**
(manuf. of branched, from carboxybisphenols)
IT **101949-49-9** 102054-11-5 102054-12-6
(branching agents, for **polycarbonates**)
IT 122-25-8 29364-82-7
(branching agents, for **polycarbonates**, manuf. of)
IT 101949-48-8P **101949-50-2P 101964-29-8P**
(manuf. of branched)